

## 1/3" Hi-re/Mid-re IR LED Weatherproof Day/Night Camera

### FEATURES:

- 380/530 TVL resolution
- 1/3" SONY Super-HAD CCD
- 4.3 mm fix lens built-in
- 20~25m IR distance capability
- 0 Lux under IR
- IP 66 fully weatherproof design



### SPECIFICATIONS:

Model No.	IRM-4380	IRM-1530
Power requirements	DC 12V	
Synchronization	Internal	
Image device	1/3" SONY Super-HAD CCD	
Picture elements	PAL: 500 x 582, NTSC: 512 x 492	PAL: 752 x 582, NTSC: 768 x 494
Scanning system	PAL: 625 lines, NTSC: 525 lines, 2:1 interlace	
Horizontal resolution	380 TV Lines	530 TV Lines
Min. illumination	IR ON, 0 Lux	
IR wavelength	850nm	
Aperture correction	Horizontal & Vertical 2H enhancer	
Signal to noise ratio	Better than 48 dB	
Auto gain control	YES	
Auto electronic shutter	AES: 1/50(60) ~1/100,000 sec.	
White balance	AWB	
Gamma correction	0.45	
Video output	1Vp-p, 75Ω composite, BNC connector	
Current	150mA OFF ,400mA ON	
Operating temperature	-10°C ~50°C (14 ~ 122 )	
IR distance	20~25m ( indoor )	
Lens	4.3mm @F1.8	
Weatherproof rate	IP 66	
Dimensions	138.3mm(Length) × 168.7mm(High)	

\*Specifications and designs are subject to change without notice.